

SPECIFICATIONS

Product Line	City Heights	Finish	Enhanced Polyurethane System
Construction	Luxury Vinyl Plank (LVP)	Installation	Glue Down
Wear Layer Thickness	12 Mil ScratchGuard	Clip System	N/A
Embossing	Natural Wood Texture	Underlayment	N/A
Edge Profile	Square Edge	Sound Properties	N/A
Overall Thickness	2mm (0.079")	Bacteria Resistance	Standard
Size (Imperial)	7" x 48"	Size (Metric)	177.8mm x 1219.2mm

PACKAGING

Pieces per Carton	15	Cartons per Container	1,500
Square Feet per Carton	37 sqft	Square Feet per Container	55,500 sqft
Square Meters per Carton	3.44 m2	Square Meters per Container	5156.12 m2
Weight per Carton (Imperial)	29 lbs	Weight per Container (Imperial)	43500 lbs
Weight per Carton (Metric)	13.15 kg	Weight per Container (Metric)	19731.27 kg
Cartons per Pallet	75	Weight per Pallet (Imperial)	2175 lbs
Square Feet per Pallet	2775 sqft	Weight per Pallet (Metric)	986.56 kg
Square Meters per Pallet	257.81 m2		

TESTING & SAFETY

Slip Resistance	ASTM D2047	>0.6 (DRY)
Radiant Flux	ASTM E648	CLASS 1
Smoke Density	ASTM E662	PASSES
Static Load	ASTM F970	2,000 PSI .005 INCH
Light Resistance	ASTM F1515	PASSES
Heat Resistance	ASTM F1514	PASSES
Chemical Resistance	ASTM F925	PASSES
Phthalates	ASTM F3414 - 20 (CPSC)	PASSES
Heavy Metals	ASTM F963	PASSES
Formaldehyde	ASTM D6007	PASSES
FloorScore Certified	California 01350	PASSES
Leed Scorecard	Eq4.3 Low-Emitting Materials	1 POINT

WARRANTY

Residential	20 Years
Light Commercial	10 Years
Commercial	None

THE MODERN FLOORING SOLUTION