

SPECIFICATIONS

Product Line	Main Street DXL GlueDown Floor
Product Type	Luxury Vinyl Plank (LVP)
Core Material	Virgin Vinyl
Fiberglass Reinforced	FiberMax DimensionLock
Wear Layer	8mil ScratchGuard
Overall Thickness	2mm (0.079")
Nominal Plank Size	7" x 48"
Actual Plank Size	177.8mm x 1219.2mm
Edge Profile	Square Edge
Embossing	Natural Wood Texture
Finish	Enhanced Polyurethane System
Bacteria Resistance	Standard
Temperature Range	45 F - 115 F
Installation Type	GlueDown with 3010 Prism, 3020 Everlast, or 3050 Omni



CARTON	
Planks	22
Square Feet	51.39 sqft
Weight (lbs)	39.02 lbs
Square Meters	4.77 m2
Weight (kg)	17.70 kg

PALLET	
Cartons	50
Square Feet	2569.5 sqft
Weight (lbs)	1984.16 lbs
Square Meters	238.5 m2
Weight (kg)	900 kg

CONTAINER	
Cartons	1,000
Square Feet	51390 sqft
Weight (lbs)	39683.16 lbs
Square Meters	4770 m2
Weight (kg)	18000 kg

PERFORMANCE TESTING

Slip Resistance	ASTM D2047	>0.66 (Dry)
Radiant Flux	ASTM E648	Class 1
Static Load	ASTM F970	2,000 PSI .005 Inch
Dimensional Stability	ASTM F2199	Pending
Smoke Density	ASTM E662	Passes
Light Resistance	ASTM F1515	Passes
Heat Resistance	ASTM F1514	Passes
Chemical Resistance	ASTM F925	Passes
Phthalates	ASTM F3414 - 20 (CPSC)	Passes
Heavy Metals	ASTM F963	Passes
Formaldehyde	ASTM D6007	Passes
FloorScore Certified	California 01350	Passes
Leed Scorecard	EQ 4.3 Low-Emitting Materials	1 Point

WARRANTY



Must use 3010 Prism, 3020 Everlast, or 3050 Omni. Refer to Warranty Guide for full details.

