

SPECIFICATIONS

Product Line	Main Street DXL
Product Type	Luxury Vinyl Plank (LVP)
Core Material	Virgin Vinyl
Fiberglass Reinforced	FiberMax DimensionLock
Wear Layer	8mil ScratchGuard
Overall Thickness	2mm (0.079")
Nominal Plank Size	7" x 48"
Actual Plank Size	177.8mm x 1219.2mm
Edge Profile	Square Edge
Embossing	Natural Wood Texture
Finish	Enhanced Polyurethane System
Bacteria Resistance	Standard
Acclimation Time	No Acclimation Required
Temperature Range	35 F - 125 F
Installation Type	GlueDown
Required Adhesive	3010 Prism, 3020 Everlast, or 3050 Omni

PERFORMANCE TESTING

Slip Resistance	ASTM D2047	>0.66 (Dry)
Radiant Flux	ASTM E648	Class 1
Static Load	ASTM F970	2,000 PSI   .005 Inch
Dimensional Stability	ASTM F2199	Pending
Dimensional Stability	Internal	< 0.03 inch
Smoke Density	ASTM E662	Passes
Light Resistance	ASTM F1515	Passes
Heat Resistance	ASTM F1514	Passes
Chemical Resistance	ASTM F925	Passes
Phthalates	ASTM F3414 - 20 (CPSC)	Passes
Heavy Metals	ASTM F963	Passes
Formaldehyde	ASTM D6007	Passes
FloorScore Certified	California 01350	Passes
Leed Scorecard	EQ 4.3 Low-Emitting Materials	1 Point



CARTON	
Planks	22
Square Feet	51.39 sqft
Weight (lbs)	39.02 lbs
Square Meters	4.77 m2
Weight (kg)	17.70 kg

PALLET	
Cartons	50
Square Feet	2569.5 sqft
Weight (lbs)	1984.16 lbs
Square Meters	238.5 m2
Weight (kg)	900 kg

CONTAINER	
Cartons	1,000
Square Feet	51390 sqft
Weight (lbs)	39683.16 lbs
Square Meters	4770 m2
Weight (kg)	18000 kg

WARRANTY



Must use 3010 Prism, 3020 Everlast, or 3050 Omni. Refer to Warranty Guide for full details.



ARCHITECTURAL SPECIFICATION

All floors shown in the finish schedule or listed in the specification shall be Main Street DXL Floor Vinyl Flooring provided by Urban Surfaces Inc., in design and color (list color TBD) selected from the range currently available from Urban Surfaces Inc, having a nominal total thickness of (Main Street DXL - 2mm-0.079"" gauge, and size in 7 in. x 48 in. (Main Street DXL - 177.8 mm x 1219.2 mm). consisting of a (Main Street DXL - 8 mil) thick wear layer over a printed film. Flooring meets composition, size, thickness, squareness, flexibility, resistance to chemicals, resistance to heat and resistance to light requirements of ASTM F 1700, "Standard Specification for Solid Vinyl Tile," Class III, Type B - Embossed Surface. For Main Street, shall have a 5-Year Limited Light Commercial warranty against manufacturing defects. For Main Street, the approved adhesives are: Prism 3010, Everlast 3020, and Omni 3050 and Underlayment FloorSilencer Pro. For additional installation, maintenance, or technical information, visit our website at [www.urbansurfaces.com](http://www.urbansurfaces.com) or contact us at 1-800-492-8722. Please view actual product samples when making a selection as our printed colors may vary from actual product.

INSTALLATION

<b>End Use:</b>	<b>Suitable Grade Level:</b>
Residential	All grades where excessive moisture conditions do not exist
<b>Installation Method:</b>	<b>Installation Sundries As Required:</b>
Glue Down	3010 Prism, 3020 Everlast, 3050 Omni, Infiniti Moisture Barrier