



Mission Bay Floating 1901 | Gluedown 1101



Carvins Cove Floating 1902 | Gluedown 1102



Sonora Heights Floating 1903 | Gluedown 1103



Newport Landing Floating 1904 | Gluedown 1104



Hansen Creek Floating 1905 | Gluedown 1105



Rochester Springs Floating 1906 | Gluedown 1106




Balboa Trails Floating 1907 | Gluedown 1107



Longview Point Floating 1908 | Gluedown 1108

PURE PRICING, PURE QUALITY

It's a new era for multi-level projects. All of the designs in the Foundations collection are available in GlueDown and Floating formats. The Foundations collection also features a wide variety of moldings and stair treads to give your projects a cohesive and polished style.



Everything Needed for Any Project



EXACT-MATCH MOLDINGS

We are proud to provide robustly built, exact-match moldings and stair-finishing options for all of our Floating Floor lines. While other manufacturers only offer "coordinated" colors, our moldings blend perfectly.



NO SUBFLOOR IS TOO TRICKY

No matter what your project needs, the versatile variety of adhesives found in our Urban Essentials line has it covered with hard-set and firm-set adhesives, integrated priming, encapsulation, moisture protection, and more.

Everlast Hard-Set Adhesive provides immediate post-install access for light traffic so spaces stay occupied.

BUILD ON A FOUNDATION OF QUALITY AND VALUE



Specifications	Floating Floor	GlueDown Floor
Product Type	Stone Polymer Composite	Luxury Vinyl Plank (LVP)
Core Material	3.5mm High-Density Solid Core	1.6mm Virgin Vinyl
Fiberglass Reinforced	N/A	FiberBlend
Wear Layer	6mil ScratchGuard	6mil ScratchGuard
Embossing	Natural Wood Texture	Natural Wood Texture
Edge Profile	Square Edge	Square Edge
Overall Thickness	4.5mm (0.177")	1.6mm (0.063")
Nominal Plank Size	7" x 48"	7" x 48"
Actual Plank Size	182mm x 1220mm	177.8mm x 1219.2mm
Finish	Enhanced Polyurethane System	Enhanced Polyurethane System
Attached Pad	1mm Sound-Reducing Pad	N/A
Clip System	Angle Angle	N/A
Testing		
Slip Resistance ASTM D2047	>0.58 (Dry)	>0.66 (Dry)
Static Loading ASTM F970	2,000 PSI .011"	2,000 PSI .005"
Radiant Flux ASTM E648	Class 1	Class 1
Smoke Density ASTM E662	Passes	Passes
Light Resistance ASTM F1515	Passes	Passes
Heat Resistance ASTM F1514	Passes	Passes
Chemical Resistance ASTM F925	Passes	Passes
Phthalates ASTM F3414 - 20 (CPSC)	Passes	Passes
Heavy Metals ASTM F963	Passes	Passes
Formaldehyde ASTM D6007	Passes	Passes
Floor Score Certified California 01350	Passes	Passes
Lead Scorecard EQ 4.3 Low-Emitting Materials	1 Point	1 Point
Warranty		
Residential	10 Years	10 Years
Light Commercial	3 Years	3 Years

