

FOUNDATIONS
6 MIL SPC FLOATING FLOOR


HANSEN CREEK
1905

URBAN
SURFACES



6
MIL


BUILD ON A FOUNDATION OF QUALITY AND VALUE



- Enhanced Polyurethane System
- 6mil ScratchGuard Wear Layer
- Natural Wood Texture
- 3.5mm High-Density Solid Core
- 1mm Sound-Reducing Underlayment



Get even better noise reduction with one of our FloorSilencer underlayments. You didn't hear it from us.



HANSEN CREEK
1905

Specifications

Floating Floor

| | |
|---------------------|-------------------------------|
| Product Type | Stone Polymer Composite |
| Core Material | 3.5mm High-Density Solid Core |
| Wear Layer | 6mil ScratchGuard |
| Embossing | Natural Wood Texture |
| Edge Profile | Square Edge |
| Overall Thickness | 4.5mm (0.177") |
| Nominal Plank Size | 7" x 48" |
| Actual Plank Size | 182mm x 1220mm |
| Finish | Enhanced Polyurethane System |
| Attached Pad | 1mm Sound-Reducing Pad |
| Clip System | Angle-Angle Clip System |
| Bacteria Resistance | Standard |

Testing

| | |
|--|-----------------------|
| Slip Resistance ASTM D2047 | >0.58 (Dry) |
| Static Loading ASTM F970 | 2,000 PSI .011 Inch |
| Radiant Flux ASTM E648 | Class 1 |
| Smoke Density ASTM E662 | Passes |
| Light Resistance ASTM F1515 | Passes |
| Heat Resistance ASTM F1514 | Passes |
| Chemical Resistance ASTM F925 | Passes |
| Phthalates ASTM F3414 - 20 (CPSC) | Passes |
| Heavy Metals ASTM F963 | Passes |
| Formaldehyde ASTM D6007 | Passes |
| Floor Score Certified California 01350 | Passes |
| Lead Scorecard EQ 4.3 | 1 Point |
| Low-Emitting Materials | |

Warranty

| | |
|------------------|----------|
| Residential | 10 Years |
| Light Commercial | 3 Years |
| Heavy Commercial | None |



FOR MORE INFO