

SPECIFICATIONS

Product Line	InstaGrip 20
Product Type	Luxury Vinyl Plank (LVP)
Core Material	4.5mm Virgin Vinyl
Fiberglass Reinforced	FiberMax
Wear Layer	20mil ScratchGuard
Overall Thickness	4.5mm (0.177")
Nominal Plank Size	9" x 60"
Actual Plank Size	228.6mm x 1524mm
Edge Profile	Beveled Edge
Embossing	Natural Wood Texture
Finish	Enhanced Polyurethane System
Installation Type	Traction / Adhesive
Bacteria Resistance	Standard



CARTON	
Planks	8
Square Feet	30.00 sqft
Weight (lbs)	50.27 lbs
Square Meters	2.79 m2
Weight (kg)	22.80 kg

PALLET	
Cartons	40
Square Feet	1200 sqft
Weight (lbs)	2050.80 lbs
Square Meters	111.6 m2
Weight (kg)	930.08 kg
CONTAINER	
Cartons	840
Square Feet	25200 sqft
Weight (lbs)	43066.80 lbs
Square Meters	2343.6 m2
Weight (kg)	19531.78 kg

PERFORMANCE TESTING

Slip Resistance	ASTM D2047	>0.69 (Dry)
Radiant Flux	ASTM E648	Class 1
Static Load	ASTM F970	2,000 PSI .011 Inch
Smoke Density	ASTM E662	Passes
Light Resistance	ASTM F1515	Passes
Heat Resistance	ASTM F1514	Passes
Chemical Resistance	ASTM F925	Passes
Phthalates	ASTM F3414 - 20 (CPSC)	Passes
Heavy Metals	ASTM F963	Passes
Formaldehyde	ASTM D6007	Passes
FloorScore Certified	California 01350	Passes
Leed Scorecard	EQ 4.3 Low-Emitting Materials	1 Point

WARRANTY



SOUND TESTING



InstaGrip 20

HIIC	IIC	LIIC	STC	ΔHIIC	ΔIIC
Pending	Pending	Pending	Pending	Pending	Pending

ARCHITECTURAL SPECIFICATION

All floors shown in the finish schedule or listed in the specification shall be InstaGrip 20 Vinyl Flooring provided by Urban Surfaces Inc., in design and color (list color TBD) selected from the range currently available from Urban Surfaces Inc, having a nominal total thickness of (InstaGrip 20- 4.5mm-0.177") gauge, and size in 9 in. x 60 in. (InstaGrip 20 - 228.6 mm x 1524 mm) consisting of a (InstaGrip 20 - 20 mil) thick wear layer over a printed film. Flooring meets composition, size, thickness, squareness, flexibility, resistance to chemicals, resistance to heat and resistance to light requirements of ASTM F 1700, "Standard Specification for Solid Vinyl Tile," Class III, Type B - Embossed Surface. For InstaGrip 20, shall have a 15-Year Limited Commercial warranty against manufacturing defects. For InstaGrip 20, the approved adhesives are: Prism 3010, Everlast 3020, Omni 3050, Subfloor Coating: Traction 3545, Underlayments: FloorSilencer Pro. For additional installation, maintenance, or technical information, visit our website at www.urbansurfaces.com or contact us at 1-800-492-8722. Please view actual product samples when making a selection as our printed colors may vary from actual product.

INSTALLATION

End Use: Residential, Light Commercial, Commercial	Suitable Grade Level: All grades where excessive moisture conditions do not exist
Installation Method: Minimal adhesive, Full glue down	Installation Sundries As Required: 3545 Traction, 3010 Prism, 3020 Everlast, 3050 Omni, Infiniti Moisture Barrier

URBAN SURFACES
2380 RAILROAD STREET BUILDING 101 CORONA, CA
(800)492.8722