

CAPE COD 1202









20 EXPERTLY ENGINEERED FOR UNRIVALED PERFORMANCE





CAPE COD 1202

Specifications	LooseLay
Product Type	Luxury Vinyl Plank (LVP)
Core Material	4.5mm Virgin Vinyl
Fiberglass Reinforced	FiberMax
Wear Layer	20mil ScratchGuard
Embossing	Natural Wood Texture
Edge Profile	Beveled Edge
Overall Thickness	4.5mm (0.177")
Nominal Plank Size	9″ x 60″
Actual Plank Size	228.6mm x 1524mm
Finish	Enhanced Polyurethane System

Testing

Slip Resistance ASTM D2047	>0.69 (Dry)
Static Loading ASTM F970	2,000 PSI .011 Inch
Radiant Flux ASTM E648	Class 1
Smoke Density ASTM E662	Passes
Light Resistance ASTM F1515	Passes
Heat Resistance ASTM F1514	Passes
Chemical Resistance ASTM F925	Passes
Phthalates ASTM F3414 - 20 (CPSC)	Passes
Heavy Metals ASTM F963	Passes
Formaldehyde ASTM D6007	Passes
Floor Score Certified California 01350	Passes
Lead Scorecard EQ 4.3 Low-Emitting Materials	1 Point



TRUE LOOSELAY IS FINALLY POSSIBLE WITH TRACTION

Traction™ provides fast and easy LooseLay installation without adhesive. This innovative anti-skid subfloor coating provides the horizontal grip strength of an adhesive with none of the permanence. LooseLay couldn't be easier.

Traction also primes the subfloor and provides up to 90% moisture protection.

Warranty

Residential	Lifetime
Light Commercial	20 Years
Heavy Commercial	15 Years







Enhanced Polyurethane System 20mil ScratchGuard Wear Layer Natural Wood Texture 4.5mm Virgin Vinyl Fiberglass Stabilization Layer

Grip-Tec Backing

