

**SPECIFICATIONS**

Product Line	<b>InstaGrip 28 Tile</b>
Product Type	<b>Luxury Vinyl Plank (LVP)</b>
Core Material	<b>5mm Virgin Vinyl</b>
Fiberglass Reinforced	<b>FiberMax</b>
Wear Layer	<b>28mil ScratchGuard</b>
Overall Thickness	<b>5mm (0.196")</b>
Nominal Plank Size	<b>36" x 36"</b>
Actual Plank Size	<b>914.4mm x 914.4mm</b>
Edge Profile	<b>Beveled Edge</b>
Embossing	<b>Natural Stone Texture</b>
Finish	<b>Enhanced Polyurethane System</b>
Installation Type	<b>Traction / Adhesive</b>
Bacteria Resistance	<b>Standard</b>



**PACKAGING**

<b>CARTON</b>	
Planks	<b>3</b>
Square Feet	<b>27.00 sqft</b>
Weight (lbs)	<b>50.04 lbs</b>
Square Meters	<b>2.51 m2</b>
Weight (kg)	<b>22.70 kg</b>

<b>PALLET</b>	
Cartons	<b>40</b>
Square Feet	<b>1080 sqft</b>
Weight (lbs)	<b>2034.86 lbs</b>
Square Meters	<b>100.4 m2</b>
Weight (kg)	<b>923 kg</b>

<b>CONTAINER</b>	
Cartons	<b>800</b>
Square Feet	<b>21600 sqft</b>
Weight (lbs)	<b>40697.29 lbs</b>
Square Meters	<b>2008 m2</b>
Weight (kg)	<b>18460 kg</b>

**PERFORMANCE TESTING**

Slip Resistance	ASTM D2047	<b>&gt;0.8 (Dry)</b>
Radiant Flux	ASTM E648	<b>Class 1</b>
Static Load	ASTM F970	<b>2,000 PSI   .008 Inch</b>
Smoke Density	ASTM E662	<b>Passes</b>
Light Resistance	ASTM F1515	<b>Passes</b>
Heat Resistance	ASTM F1514	<b>Passes</b>
Chemical Resistance	ASTM F925	<b>Passes</b>
Phthalates	ASTM F3414 - 20 (CPSC)	<b>Passes</b>
Heavy Metals	ASTM F963	<b>Passes</b>
Formaldehyde	ASTM D6007	<b>Passes</b>
FloorScore Certified	California 01350	<b>Passes</b>
Leed Scorecard	EQ 4.3 Low-Emitting Materials	<b>1 Point</b>

**WARRANTY**



**SOUND TESTING**



InstaGrip 28 Tile

HIIC	IIC	LIIC	STC	ΔHIIC	ΔIIC
Pending	48	Pending	61	Pending	11

## ARCHITECTURAL SPECIFICATION

---

All floors shown in the finish schedule or listed in the specification shall be InstaGrip 28 Tile Vinyl Flooring provided by Urban Surfaces Inc., in design and color (list color TBD) selected from the range currently available from Urban Surfaces Inc, having a nominal total thickness of (InstaGrip 28 Tile - 5mm-0.196") gauge, and size 36 in. x 36 in. (InstaGrip 28 Tile - 914.4 mm x 914.4 mm) consisting of a (InstaGrip 28 Tile - 28 mil) thick wear layer over a printed film. Flooring meets composition, size, thickness, squareness, flexibility, resistance to chemicals, resistance to heat and resistance to light requirements of ASTM F 1700, "Standard Specification for Solid Vinyl Tile," Class III, Type B - Embossed Surface. For InstaGrip 28 Tile, shall have a 20-Year Limited Commercial warranty against manufacturing defects. For InstaGrip 28 Tile, the approved adhesives are: Prism 3010, Everlast 3020, Omni 3050, Subfloor Coating: Traction 3545 Underlayments: FloorSilencer Pro. For additional installation, maintenance, or technical information, visit our website at [www.urbansurfaces.com](http://www.urbansurfaces.com) or contact us at 1-800-492-8722. Please view actual product samples when making a selection as our printed colors may vary from actual product.

## INSTALLATION

---

<b>End Use:</b> Residential, Light Commercial, Heavy Commercial	<b>Suitable Grade Level:</b> All grades where excessive moisture conditions do not exist
<b>Installation Method:</b> Minimal adhesive, Full glue down	<b>Installation Sundries As Required:</b> 3545 Traction, 3010 Prism, 3020 Everlast, 3050 Omni, Infiniti Moisture Barrier

**URBAN SURFACES**  
2380 RAILROAD STREET BUILDING 101 CORONA, CA  
(800)492.8722