

## SPECIFICATIONS

Product Line	<b>InstaGrip 28</b>	Edge Profile	<b>Beveled Edge</b>
Product Type	<b>Luxury Vinyl Plank (LVP)</b>	Embossing	<b>Natural Wood Texture</b>
Core Material	<b>5mm Virgin Vinyl</b>	Finish	<b>Enhanced Polyurethane System</b>
Fiberglass Reinforced	<b>FiberMax</b>	Installation	<b>Traction / Adhesive</b>
Wear Layer	<b>28mil ScratchGuard</b>	Clip System	<b>N/A</b>
Overall Thickness	<b>5mm (0.196")</b>	Bacteria Resistance	<b>Standard</b>
Nominal Plank Size	<b>9" x 48"</b>	Attached Pad	<b>N/A</b>
Actual Plank Size	<b>228.6mm x 1219.2mm</b>		

## PACKAGING

	Units	Square Feet	Weight (lbs)	Square Meters	Weight (kg)
Carton	<b>8</b>	<b>24 sqft</b>	<b>41 lbs</b>	<b>2.23 m2</b>	<b>18.6 kg</b>
Pallet	<b>52</b>	<b>1248 sqft</b>	<b>2132 lbs</b>	<b>115.94 m2</b>	<b>967.06 kg</b>
Container	<b>1,040</b>	<b>24960 sqft</b>	<b>42640 lbs</b>	<b>2318.86 m2</b>	<b>19341.18 kg</b>

## PERFORMANCE & TESTING

Slip Resistance	ASTM D2047	<b>&gt;0.8 (Dry)</b>
Radiant Flux	ASTM E648	<b>Class 1</b>
Static Load	ASTM F970	<b>2,000 PSI   .008 Inch</b>
Smoke Density	ASTM E662	<b>Passes</b>
Light Resistance	ASTM F1515	<b>Passes</b>
Heat Resistance	ASTM F1514	<b>Passes</b>
Chemical Resistance	ASTM F925	<b>Passes</b>
Phthalates	ASTM F3414 - 20 (CPSC)	<b>Passes</b>
Heavy Metals	ASTM F963	<b>Passes</b>
Formaldehyde	ASTM D6007	<b>Passes</b>
FloorScore Certified	California 01350	<b>Passes</b>
Leed Scorecard	EQ 4.3 Low-Emitting Materials	<b>1 Point</b>

## WARRANTY

Residential	<b>Lifetime</b>
Light Commercial	<b>Lifetime</b>
Heavy Commercial	<b>20 Years</b>