

SPECIFICATIONS

Product Line	InstaGrip	Finish	Enhanced Polyurethane System
Construction	Luxury Vinyl Plank (LVP)	Installation	Minimal / Full Spread Adhesive
Wear Layer	28 Mil ScratchGuard	Clip System	N/A
Embossing	Natural Wood Texture	Underlayment	N/A
Edge Profile	Beveled Edge	Sound Properties	STC 61 IIC 48 ΔIIC 11
Overall Thickness	5mm (0.196)	Bacteria Resistance	Standard
Plank Size	9 x 48		

PACKAGING

	Units	Square Feet	Weight (lbs)	Square Meters	Weight (kg)
Carton	8 Planks	24 sqft	41 lbs	2.23 m2	18.6 kg
Pallet	52 Cartons	1248 sqft	2132 lbs	115.94 m2	967.06 kg
Container	1,040 Cartons	24960 sqft	42640 lbs	2318.86 m2	19341.18 kg

PERFORMANCE & TESTING

Slip Resistance	ASTM D2047	>0.8 (Dry)
Radiant Flux	ASTM E648	Class 1
Static Load	ASTM F970	2,000 PSI .008 Inch
Smoke Density	ASTM E662	Passes
Light Resistance	ASTM F1515	Passes
Heat Resistance	ASTM F1514	Passes
Chemical Resistance	ASTM F925	Passes
Phthalates	ASTM F3414 - 20 (CPSC)	Passes
Heavy Metals	ASTM F963	Passes
Formaldehyde	ASTM D6007	Passes
FloorScore Certified	California 01350	Passes
Leed Scorecard	EQ 4.3 Low-Emitting Materials	1 Point

WARRANTY

Residential	Lifetime
Light Commercial	Lifetime
Commercial	20 Years