

SPECIFICATIONS

Product Line	Level Seven	Finish	Enhanced Polyurethane System
Construction	Luxury Vinyl Plank (LVP)	Installation	Glue Down
Wear Layer Thickness	20 Mil ScratchGuard	Clip System	N/A
Embossing	Natural Wood Texture	Underlayment	N/A
Edge Profile	Beveled Edge	Sound Properties	N/A
Overall Thickness	3mm (0.118")	Bacteria Resistance	Standard
Size (Imperial)	7" x 48"	Size (Metric)	177.8mm x 1219.2mm

PACKAGING

Pieces per Carton	14	Cartons per Container	1,140
Square Feet per Carton	34.6 sqft	Square Feet per Container	39444 sqft
Square Meters per Carton	3.21 m2	Square Meters per Container	3664.47 m2
Weight per Carton (Imperial)	39 lbs	Weight per Container (Imperial)	44460 lbs
Weight per Carton (Metric)	17.69 kg	Weight per Container (Metric)	20166.72 kg
Cartons per Pallet	60	Weight per Pallet (Imperial)	2340 lbs
Square Feet per Pallet	2076 sqft	Weight per Pallet (Metric)	1061.41 kg
Square Meters per Pallet	192.87 m2		

TESTING & SAFETY

Slip Resistance	ASTM D2047	>0.6 (DRY)
Radiant Flux	ASTM E648	CLASS 1
Smoke Density	ASTM E662	PASSES
Static Load	ASTM F970	2,000 PSI .005 INCH
Light Resistance	ASTM F1515	PASSES
Heat Resistance	ASTM F1514	PASSES
Chemical Resistance	ASTM F925	PASSES
Phthalates	ASTM F3414 - 20 (CPSC)	PASSES
Heavy Metals	ASTM F963	PASSES
Formaldehyde	ASTM D6007	PASSES
FloorScore Certified	California 01350	PASSES
Leed Scorecard	Eq4.3 Low-Emitting Materials	1 POINT

WARRANTY

Residential	Lifetime
Light Commercial	20 Years
Commercial	15 Years

THE MODERN FLOORING SOLUTION