

SPECIFICATIONS

Product Line	Main Street (O)	Finish	Enhanced Polyurethane System
Construction	Luxury Vinyl Plank (LVP)	Installation	GlueDown
Wear Layer	8 Mil ScratchGuard	Clip System	N/A
Embossing	Natural Wood Texture	Underlayment	N/A
Edge Profile	Square Edge	Sound Properties	N/A
Overall Thickness	2mm (0.079)	Bacteria Resistance	Standard
Plank Size	7 x 48		

PACKAGING

	Units	Square Feet	Weight (lbs)	Square Meters	Weight (kg)
Carton	22 Planks	51.39 sqft	39 lbs	4.77 m2	17.7 kg
Pallet	50 Cartons	2569 sqft	1993 lbs	239 m2	903.6 kg
Container	1,000 Cartons	51387 sqft	39842 lbs	4774 m2	18072 kg

PERFORMANCE & TESTING

Slip Resistance	ASTM D2047	>0.6 (Dry)
Radiant Flux	ASTM E648	Class 1
Static Load	ASTM F970	2,000 PSI .005 Inch
Smoke Density	ASTM E662	Passes
Light Resistance	ASTM F1515	Passes
Heat Resistance	ASTM F1514	Passes
Chemical Resistance	ASTM F925	Passes
Phthalates	ASTM F3414 - 20 (CPSC)	Passes
Heavy Metals	ASTM F963	Passes
Formaldehyde	ASTM D6007	Passes
FloorScore Certified	California 01350	Passes
Leed Scorecard	EQ 4.3 Low-Emitting Materials	1 Point

WARRANTY

Residential	15 Years
Light Commercial	5 Years
Commercial	None