

## SPECIFICATIONS

Product Line	<b>Main Street</b>
Product Type	<b>Luxury Vinyl Plank (LVP)</b>
Core Material	<b>2mm Virgin Vinyl</b>
Fiberglass Reinforced	<b>FiberBlend</b>
Wear Layer	<b>8mil ScratchGuard</b>
Overall Thickness	<b>2mm (0.079")</b>
Nominal Plank Size	<b>7" x 48"</b>
Actual Plank Size	<b>177.8mm x 1219.2mm</b>
Edge Profile	<b>Square Edge</b>
Embossing	<b>Natural Wood Texture</b>
Finish	<b>Enhanced Polyurethane System</b>
Installation Type	<b>GlueDown</b>
Bacteria Resistance	<b>Standard</b>



**PACKAGING**

<b>CARTON</b>	
Planks	<b>22</b>
Square Feet	<b>51.39 sqft</b>
Weight (lbs)	<b>39.02 lbs</b>
Square Meters	<b>4.77 m2</b>
Weight (kg)	<b>17.70 kg</b>

<b>PALLET</b>	
Cartons	<b>50</b>
Square Feet	<b>2569.5 sqft</b>
Weight (lbs)	<b>1984.16 lbs</b>
Square Meters	<b>238.5 m2</b>
Weight (kg)	<b>900 kg</b>

<b>CONTAINER</b>	
Cartons	<b>1,000</b>
Square Feet	<b>51390 sqft</b>
Weight (lbs)	<b>39683.16 lbs</b>
Square Meters	<b>4770 m2</b>
Weight (kg)	<b>18000 kg</b>

## PERFORMANCE TESTING

Slip Resistance	ASTM D2047	<b>&gt;0.6 (Dry)</b>
Radiant Flux	ASTM E648	<b>Class 1</b>
Static Load	ASTM F970	<b>2,000 PSI   .005 Inch</b>
Smoke Density	ASTM E662	<b>Passes</b>
Light Resistance	ASTM F1515	<b>Passes</b>
Heat Resistance	ASTM F1514	<b>Passes</b>
Chemical Resistance	ASTM F925	<b>Passes</b>
Phthalates	ASTM F3414 - 20 (CPSC)	<b>Passes</b>
Heavy Metals	ASTM F963	<b>Passes</b>
Formaldehyde	ASTM D6007	<b>Passes</b>
FloorScore Certified	California 01350	<b>Passes</b>
Leed Scorecard	EQ 4.3 Low-Emitting Materials	<b>1 Point</b>

## WARRANTY

<b>15</b> FIFTEEN YEARS	<b>05</b> FIVE YEARS	<b>00</b> NONE
RESIDENTIAL	LIGHT COMMERCIAL	HEAVY COMMERCIAL

WATERPROOF	PET FRIENDLY	EASY REPAIR
------------	--------------	-------------

## ARCHITECTURAL SPECIFICATION

---

All floors shown in the finish schedule or listed in the specification shall be Main Street Floor Vinyl Flooring provided by Urban Surfaces Inc., in design and color (list color TBD) selected from the range currently available from Urban Surfaces Inc, having a nominal total thickness of (Main Street - 2mm-0.079") gauge, and size in 7 in. x 48 in. (Main Street - 177.8 mm x 1219.2 mm). consisting of a (Main Street - 8 mil) thick wear layer over a printed film. Flooring meets composition, size, thickness, squareness, flexibility, resistance to chemicals, resistance to heat and resistance to light requirements of ASTM F 1700, "Standard Specification for Solid Vinyl Tile," Class III, Type B - Embossed Surface. For Main Street, shall have a 5-Year Limited Light Commercial warranty against manufacturing defects. For Main Street, the approved adhesives are: Prism 3010, Everlast 3020, and Omni 3050 and Underlayment FloorSilencer Pro. For additional installation, maintenance, or technical information, visit our website at [www.urbansurfaces.com](http://www.urbansurfaces.com) or contact us at 1-800-492-8722. Please view actual product samples when making a selection as our printed colors may vary from actual product.

## INSTALLATION

---

**End Use:**

Residential

**Suitable Grade Level:**

All grades where excessive moisture conditions do not exist

**Installation Method:**

Glue Down

**Installation Sundries As Required:**

3010 Prism, 3020 Everlast, 3050 Omni, Infiniti Moisture Barrier

**URBAN SURFACES**  
2380 RAILROAD STREET BUILDING 101 CORONA, CA  
(800)492.8722