

# **HUDSON** 8071









# **NATURAL ELEGANCE FOR ANY RESIDENCE**



**HUDSON** 8071

**Specifications** 

**Fiberglass Reinforced** 

Product Type Core Material

Wear Layer

Embossing

Edge Profile

**Overall Thickness** 

Actual Plank Size

Nominal Plank Size



GlueDown

2mm Virgin Vinyl

8mil ScratchGuard

Natural Wood Texture

177.8mm x 1219.2mm

**Enhanced Polyurethane System** 

FiberBlend

Square Edge

2mm (0.079")

7" x 48"

Luxury Vinyl Plank (LVP)



Enhanced Polyurethane System

8mil ScratchGuard Wear Layer

Natural Wood Texture

2mm Virgin Vinyl



### Testing

Finish

•	
Slip Resistance ASTM D2047	>0.6 (Dry)
Static Loading ASTM F970	2,000 PSI   .005 Inch
Radiant Flux ASTM E648	Class 1
Smoke Density ASTM E662	Passes
Light Resistance ASTM F1515	Passes
Heat Resistance ASTM F1514	Passes
Chemical Resistance ASTM F925	Passes
Phthalates ASTM F3414 - 20 (CPSC)	Passes
Heavy Metals ASTM F963	Passes
Formaldehyde ASTM D6007	Passes
Floor Score Certified California 01350	Passes
Lead Scorecard EQ 4.3 Low-Emitting Materials	1 Point

#### Warranty

Residential	15 Years
Light Commercial	5 Years
Heavy Commercial	None







# **EVERLAST IS HERE TO STAY**

Everlast is true to its name with its heavy-duty, hard-set bond that handles both light-traffic and commercial applications with heavy rolling loads.

Everlast Hard-Set Adhesive provides immediate post-install access for light traffic so spaces stay occupied.



## TRILOGY IS WHAT YOU NEED IT TO BE

Trilogy primes for an effective adhesive bond, setting the stage for Everlast to effectively and securely bond GlueDown LVP to the subfloor.

Provides encapsulation or up to 95% moisture protection (not simultaneously).