

**SPECIFICATIONS**

<b>Product Line</b>	Main Street	<b>Finish</b>	Enhanced Polyurethane System
<b>Construction</b>	Luxury Vinyl Plank (LVP)	<b>Installation</b>	Glue Down
<b>Wear Layer Thickness</b>	8 Mil ScratchGuard	<b>Clip System</b>	N/A
<b>Embossing</b>	Natural Wood Texture	<b>Underlayment</b>	N/A
<b>Edge Profile</b>	Square Edge	<b>Sound Properties</b>	N/A
<b>Overall Thickness</b>	2mm (0.079")	<b>Bacteria Resistance</b>	Standard
<b>Size (Imperial)</b>	7" x 48"	<b>Size (Metric)</b>	177.8mm x 1219.2mm

**PACKAGING**

<b>Pieces per Carton</b>	15	<b>Cartons per Container</b>	1500
<b>Square Feet per Carton</b>	37 sqft	<b>Square Feet per Container</b>	55500 sqft
<b>Square Meters per Carton</b>	3.44 m2	<b>Square Meters per Container</b>	5156.12 m2
<b>Weight per Carton (Imperial)</b>	29 lbs	<b>Weight per Container (Imperial)</b>	43500 lbs
<b>Weight per Carton (Metric)</b>	13.15 kg	<b>Weight per Container (Metric)</b>	19731.27 kg
<b>Cartons per Pallet</b>	75	<b>Weight per Pallet (Imperial)</b>	2175 lbs
<b>Square Feet per Pallet</b>	2775 sqft	<b>Weight per Pallet (Metric)</b>	986.56 kg
<b>Square Meters per Pallet</b>	257.81 m2		

**TESTING & SAFETY**

<b>Slip Resistance</b>	ASTM D2047	>0.6 (DRY)
<b>Radiant Flux</b>	ASTM E648	CLASS 1
<b>Smoke Density</b>	ASTM E662	PASSES
<b>Static Load</b>	ASTM F970	2,000 PSI   .005 INCH
<b>Light Resistance</b>	ASTM F1515	PASSES
<b>Heat Resistance</b>	ASTM F1514	PASSES
<b>Chemical Resistance</b>	ASTM F925	PASSES
<b>Phthalates</b>	ASTM F3414 - 20 (CPSC)	PASSES
<b>Heavy Metals</b>	ASTM F963	PASSES
<b>Formaldehyde</b>	ASTM D6007	PASSES
<b>FloorScore Certified</b>	California 01350	PASSES
<b>Leed Scorecard</b>	Eq4.3 Low-Emitting Materials	1 POINT

**WARRANTY**

<b>Residential</b>	15 Years
<b>Light Commercial</b>	5 Years
<b>Commercial</b>	None

THE **MODERN FLOORING** SOLUTION