

SPECIFICATIONS

Product Line	SoHo Square
Product Type	Luxury Vinyl Plank (LVP)
Core Material	3mm Virgin Vinyl
Fiberglass Reinforced	FiberBlend
Wear Layer	20mil ScratchGuard
Overall Thickness	3mm (0.118")
Nominal Plank Size	7" x 48"
Actual Plank Size	177.8mm x 1219.2mm
Edge Profile	Square Edge
Embossing	Natural Wood Texture
Finish	Enhanced Polyurethane System
Installation Type	GlueDown
Bacteria Resistance	Standard



CARTON	
Planks	15
Square Feet	35.00 sqft
Weight (lbs)	40.12 lbs
Square Meters	3.25 m2
Weight (kg)	18.20 kg

PALLET	
Cartons	55
Square Feet	1925 sqft
Weight (lbs)	2239.95 lbs
Square Meters	178.75 m2
Weight (kg)	1016.03 kg

CONTAINER	
Cartons	1,100
Square Feet	38500 sqft
Weight (lbs)	44799.08 lbs
Square Meters	3575 m2
Weight (kg)	20320.55 kg

PERFORMANCE TESTING

Slip Resistance	ASTM D2047	>0.69 (Dry)
Radiant Flux	ASTM E648	Class 1
Static Load	ASTM F970	2,000 PSI .011 Inch
Smoke Density	ASTM E662	Passes
Light Resistance	ASTM F1515	Passes
Heat Resistance	ASTM F1514	Passes
Chemical Resistance	ASTM F925	Passes
Phthalates	ASTM F3414 - 20 (CPSC)	Passes
Heavy Metals	ASTM F963	Passes
Formaldehyde	ASTM D6007	Passes
FloorScore Certified	California 01350	Passes
Leed Scorecard	EQ 4.3 Low-Emitting Materials	1 Point

WARRANTY

LIFE TIME	20 YEARS	15 YEARS
RESIDENTIAL	LIGHT COMMERCIAL	HEAVY COMMERCIAL



SOUND TESTING



SoHo Square + FloorSilencer Pro

HIIC	IIC	LIIC	STC	ΔHIIC	ΔIIC
70	67	70	61	27	23

ARCHITECTURAL SPECIFICATION

All floors shown in the finish schedule or listed in the specification shall be SoHo Square Floor Vinyl Flooring provided by Urban Surfaces Inc., in design and color (list color TBD) selected from the range currently available from Urban Surfaces Inc, having a nominal total thickness of (SoHo Square - 3mm-0.118") gauge, and size in 7 in. x 48 in. (SoHo Square - 177.8 mm x 1219.2 mm). consisting of a (SoHo Square - 20 mil) thick wear layer over a printed film. Flooring meets composition, size, thickness, squareness, flexibility, resistance to chemicals, resistance to heat and resistance to light requirements of ASTM F 1700, "Standard Specification for Solid Vinyl Tile," Class III, Type B - Embossed Surface. For SoHo Square, shall have a 15-Year Limited Commercial warranty against manufacturing defects. For SoHo Square, the approved adhesives are: Prism 3010, Everlast 3020, and Omni 3050 and Underlayment FloorSilencer Pro. For additional installation, maintenance, or technical information, visit our website at www.urbansurfaces.com or contact us at 1-800-492-8722. Please view actual product samples when making a selection as our printed colors may vary from actual product.

INSTALLATION

End Use:

Residential, Light Commercial,
Commercial

Suitable Grade Level:

All grades where excessive moisture
conditions do not exist

Installation Method:

Glue Down

Installation Sundries As Required:

3010 Prism, 3020 Everlast, 3050 Omni,
Infiniti Moisture Barrier

URBAN SURFACES
2380 RAILROAD STREET BUILDING 101 CORONA, CA
(800)492.8722