

CANAL STREET 7501











AT THE INTERSECTION OF ART AND INDUSTRY





CANAL STREET

7501



Enhanced Polyurethane System

20mil ScratchGuard Wear Layer

Natural Wood Texture

3mm Virgin Vinyl





EVERLAST IS HERE TO STAY

Everlast is true to its name with its heavy-duty, hard-set bond that handles both light-traffic and commercial applications with heavy rolling loads.

Everlast Hard-Set Adhesive provides immediate post-install access for light traffic so spaces stay occupied.



TRILOGY IS WHAT YOU NEED IT TO BE

Trilogy primes for an effective adhesive bond, setting the stage for Everlast to effectively and securely bond GlueDown LVP to the subfloor.

Provides encapsulation or up to 95% moisture protection (not simultaneously).

Specifications	GlueDown
Product Type	Luxury Vinyl Plank (LVP)
Core Material	3mm Virgin Vinyl
Fiberglass Reinforced	FiberBlend
Wear Layer	20mil ScratchGuard
Embossing	Natural Wood Texture
Edge Profile	Square Edge
Overall Thickness	3mm (0.118")
Nominal Plank Size	7" x 48"
Actual Plank Size	177.8mm x 1219.2mm
Finish	Enhanced Polyurethane System

Testing

Static Loading ASTM F970 2,000 PSI .011 Inc Radiant Flux ASTM E648 Smoke Density ASTM E662 Light Resistance ASTM F1515 Heat Resistance ASTM F1514 Chemical Resistance ASTM F925 Phthalates ASTM F3414 - 20 (CPSC) Heavy Metals ASTM F963 Formaldehyde ASTM D6007 Passe Floor Score Certified California 01350 Lead Scorecard EQ 4.3	Slip Resistance ASTM D2047	>0 (0 (Dm)
Radiant Flux ASTM E648 Class Smoke Density ASTM E662 Light Resistance ASTM F1515 Passe Heat Resistance ASTM F1514 Chemical Resistance ASTM F925 Phthalates ASTM F3414 - 20 (CPSC) Passe Heavy Metals ASTM F963 Formaldehyde ASTM D6007 Passe Floor Score Certified California 01350 Lead Scorecard EQ 4.3	Slip Resistance ASTM D2047	>0.69 (Dry)
Smoke Density ASTM E662 Light Resistance ASTM F1515 Passe Heat Resistance ASTM F1514 Chemical Resistance ASTM F925 Phthalates ASTM F3414 - 20 (CPSC) Heavy Metals ASTM F963 Formaldehyde ASTM D6007 Passe Floor Score Certified California 01350 Lead Scorecard EQ 4.3	Static Loading ASTM F970	2,000 PSI .011 Inch
Light Resistance ASTM F1515 Heat Resistance ASTM F1514 Chemical Resistance ASTM F925 Phthalates ASTM F3414 - 20 (CPSC) Heavy Metals ASTM F963 Formaldehyde ASTM D6007 Floor Score Certified California 01350 Lead Scorecard EQ 4.3	Radiant Flux ASTM E648	Class 1
Passe Chemical Resistance ASTM F1514 Passe Chemical Resistance ASTM F925 Phthalates ASTM F3414 - 20 (CPSC) Passe Heavy Metals ASTM F963 Pormaldehyde ASTM D6007 Passe Floor Score Certified California 01350 Passe Lead Scorecard EQ 4.3	Smoke Density ASTM E662	Passes
Chemical Resistance ASTM F925 Phthalates ASTM F3414 - 20 (CPSC) Passe Heavy Metals ASTM F963 Passe Formaldehyde ASTM D6007 Passe Floor Score Certified California 01350 Passe Lead Scorecard EQ 4.3	Light Resistance ASTM F1515	Passes
Phthalates ASTM F3414 - 20 (CPSC) Heavy Metals ASTM F963 Passe Formaldehyde ASTM D6007 Passe Floor Score Certified California 01350 Lead Scorecard EQ 4.3 Passe 1 Poir	Heat Resistance ASTM F1514	Passes
Heavy Metals ASTM F963 Formaldehyde ASTM D6007 Passe Floor Score Certified California 01350 Lead Scorecard EQ 4.3 Passe 1 Poir	Chemical Resistance ASTM F925	Passes
Formaldehyde ASTM D6007 Passe Floor Score Certified California 01350 Lead Scorecard EQ 4.3 1 Poir	Phthalates ASTM F3414 - 20 (CPSC)	Passes
Floor Score Certified California 01350 Passe Lead Scorecard EQ 4.3 1 Poir	Heavy Metals ASTM F963	Passes
Lead Scorecard EQ 4.3 1 Poir	Formaldehyde ASTM D6007	Passes
	Floor Score Certified California 01350	Passes
	Lead Scorecard EQ 4.3 Low-Emitting Materials	1 Point

Warranty

Residential	Lifetime	
Light Commercial	20 Years	
Heavy Commercial	15 Years	





