

SPECIFICATIONS

Product Line	Solid State Wood Composite Floor	Wear Resistance	AC4 Superior Resistance
Texture	Natural Wood Registered Emboss	Installation	Floating
Edge Profile	Beveled Edge	Clip System	Uniclic
Overall Thickness	9mm (0.354")	Attached Pad	1mm Sound-Reducing Pad
Plank Size	7.68" x 47.83"	Sound Properties	Test Results Pending
Core	High Density Fiberboard (HDF)		

Note: Moisture barrier required where subfloor moisture levels exceed warranty guidelines

PACKAGING

	Units	Square Feet	Weight (lbs)	Square Meters	Weight (kg)
Carton	7 Planks	17.85 sqft	29.98 lbs	1.659 m2	13.60 kg
Pallet	75 Cartons	1338.75 sqft	2248.5 lbs	124.425 m2	1020 kg
Container	1500 Cartons	26775 sqft	44970 lbs	2488.5 m2	20400 kg

PERFORMANCE & TESTING

FloorScore Certified	California 01350	Certified
Leed Scorecard	EQ 4.3 Low-Emitting Materials	1 Point
CARB II Compliant	ATCM 93120	Yes
EPA TSCA Title VI Compliant	US EPA 40 CFR Part 770, Title VI	Yes
Responsible Forestry	FSC A000525	FSC 100%
Static Load	NALFA 3.1	≥ 1160 PSI
Thickness Swell	NALFA 3.2	≤ 12%
Light Resistance	NALFA 3.3	No More than Slight Effect
Cleanability/Stain Resistance	NALFA 3.4	< 20 No More than Slight Effect
Large Ball Impact Resistance	NALFA 3.5	> 1400 mm (55.1 inch)
Small Ball Impact Resistance	NALFA 3.6	> 500 mm (19.7 inch)
Wear Resistance	NALFA 3.7	≥ 6000 cycles
Dimensional Tolerance	NALFA 3.8	Meets Class 4 Requirements
Castor Chair Resistance	NALFA 3.9	35,000 cycles, No Effect
Surface Bond	NALFA 3.10	1.04 N/mm²
Formaldehyde	ASTM D6007	Passes

WARRANTY

Residential

Lifetime