

SPECIFICATIONS

Product Line	Sound-Tec Tile	Finish	Anti-Microbial + Ceramic Bead
Construction	Stone Polymer Composite (SPC)	Installation	Floating
Wear Layer	20 Mil ScratchGuard	Clip System	Rapid Lock
Embossing	Natural Wood Texture	Underlayment	Sound Reducing + Anti Microbial
Edge Profile	Beveled Edge	Sound Properties	STC 61 IIC 66 ΔIIC 21
Overall Thickness	6mm (0.236)	Bacteria Resistance	Bioshield Coat
Plank Size	12 x 24		

PACKAGING

	Units	Square Feet	Weight (lbs)	Square Meters	Weight (kg)
Carton	12 Planks	24 sqft	45 lbs	2.23 m2	20.41 kg
Pallet	54 Cartons	1296 sqft	2430 lbs	120.4 m2	1102.23 kg
Container	1,026 Cartons	24624 sqft	46170 lbs	2287.64 m2	20942.36 kg

PERFORMANCE & TESTING

Slip Resistance	ASTM D2047	>0.52 (Dry)
Radiant Flux	ASTM E648	Class 1
Static Load	ASTM F970	2,000 PSI .036 Inch
Smoke Density	ASTM E662	Passes
Light Resistance	ASTM F1515	Passes
Heat Resistance	ASTM F1514	Passes
Chemical Resistance	ASTM F925	Passes
Phthalates	ASTM F3414 - 20 (CPSC)	Passes
Heavy Metals	ASTM F963	Passes
Formaldehyde	ASTM D6007	Passes
FloorScore Certified	California 01350	Passes
Leed Scorecard	EQ 4.3 Low-Emitting Materials	1 Point

WARRANTY

Residential	Lifetime
Light Commercial	20 Years
Commercial	15 Years