

SPECIFICATIONS

Product Line	Sound-Tec Tile
Product Type	Stone Polymer Composite
Core Material	4.5mm High-Density Solid Core
Wear Layer	20mil ScratchGuard
Overall Thickness	6mm (0.236")
Nominal Plank Size	12" x 24"
Actual Plank Size	305mm x 609mm
Edge Profile	Beveled Edge
Embossing	Natural Stone Texture
Finish	Antimicrobial + Ceramic Bead
Installation Type	Floating
Clip System	Angle-Drop Clip System
Bacteria Resistance	Bioshield Coat
Attached Pad	1.5mm Sound-Reducing & Antimicrobial Pad



PACKAGING

CARTON	
Planks	12
Square Feet	23.99 sqft
Weight (lbs)	44.97 lbs
Square Meters	2.23 m2
Weight (kg)	20.40 kg

PALLET	
Cartons	54
Square Feet	1295.46 sqft
Weight (lbs)	2480.2 lbs
Square Meters	120.42 m2
Weight (kg)	1125 kg

CONTAINER	
Cartons	1,026
Square Feet	24613.74 sqft
Weight (lbs)	47123.75 lbs
Square Meters	2287.98 m2
Weight (kg)	21375 kg

PERFORMANCE TESTING

Slip Resistance	ASTM D2047	>0.52 (Dry)
Radiant Flux	ASTM E648	Class 1
Static Load	ASTM F970	2,000 PSI .036 Inch
Smoke Density	ASTM E662	Passes
Light Resistance	ASTM F1515	Passes
Heat Resistance	ASTM F1514	Passes
Chemical Resistance	ASTM F925	Passes
Phthalates	ASTM F3414 - 20 (CPSC)	Passes
Heavy Metals	ASTM F963	Passes
Formaldehyde	ASTM D6007	Passes
FloorScore Certified	California 01350	Passes
Leed Scorecard	EQ 4.3 Low-Emitting Materials	1 Point

WARRANTY

LIFE TIME RESIDENTIAL **20 YEARS** LIGHT COMMERCIAL **15 YEARS** HEAVY COMMERCIAL

WATERPROOF **PET FRIENDLY** **ANTIMICROBIAL**

SOUND TESTING



Sound-Tec Tile 20mil SPC Floor
Sound-Tec Tile + FloorSilencer Flex
Sound-Tec Tile + FloorSilencer Boost

HIIC	IIC	LIIC	STC	ΔHIIC	ΔIIC
69	64	75	61	28	24
77	66	77	60	35	25
78	66	75	61	41	24

ARCHITECTURAL SPECIFICATION

All floors shown in the finish schedule or listed in the specification shall be Sound-Tec Tile SPC Flooring provided by Urban Surfaces Inc., in design and color (list color TBD) selected from the range currently available from Urban Surfaces Inc, having a nominal total thickness of (Sound-Tec Tile- 6mm-0.236") gauge, and size in 12 in. x 24 in. (Sound-Tec Tile - 305 mm x 609 mm) consisting of a (Sound-Tec Tile - 20 mil) thick wear layer over a printed film. Flooring meets composition, size, thickness, squareness, flexibility, resistance to chemicals, resistance to heat and resistance to light requirements of ASTM F 1700, "Standard Specification for Solid Vinyl Tile," Class III, Type B - Embossed Surface. For Sound-Tec Tile, shall have a 15-Year Limited Commercial warranty against manufacturing defects. For Sound-Tec Tile, the Underlayment shall be FloorSilencer Flex/ FloorSilencer Boost/ Floor Silencer Pro For additional installation, maintenance, or technical information, visit our website at www.urbansurfaces.com or contact us at 1-800-492-8722. Please view actual product samples when making a selection as our printed colors may vary from actual product.

INSTALLATION

End Use: Residential, Light Commercial	Suitable Grade Level: All grades where excessive moisture conditions do not exist
Installation Method: Direct Float, Click Lock System	Installation Sundries As Required: FloorSilencer Boost, FloorSilencer Flex, FloorSilencer Pro

URBAN SURFACES
2380 RAILROAD STREET BUILDING 101 CORONA, CA
(800)492.8722