

METEOR 9604









FOR KITCHENS, BATHS, AND FINE ART GALLERIES





METEOR

| Specifications | Floating Floor |
|---------------------|--|
| Product Type | Stone Polymer Composite |
| Core Material | 4.5mm High-Density Solid Core |
| Wear Layer | 20mil ScratchGuard |
| Embossing | Natural Stone Texture |
| Edge Profile | Beveled Edge |
| Overall Thickness | 6mm (0.236") |
| Nominal Plank Size | 12" x 24" |
| Actual Plank Size | 305mm x 609mm |
| Finish | Antimicrobial + Ceramic Bead |
| Attached Pad | 1.5mm Sound-Reducing & Antimicrobial Pad |
| Clip System | Angle-Drop Clip System |
| Bacteria Resistance | Bioshield Coat |

Testing

| Slip Resistance ASTM D2047 | >0.52 (Dry) |
|---|-----------------------|
| Silp Resistance AS I'M D204/ | ••••=(•••) |
| Static Loading ASTM F970 | 2,000 PSI .036 Inch |
| Radiant Flux ASTM E648 | Class 1 |
| Smoke Density ASTM E662 | Passes |
| Light Resistance ASTM F1515 | Passes |
| Heat Resistance ASTM F1514 | Passes |
| Chemical Resistance ASTM F925 | Passes |
| Phthalates ASTM F3414 - 20 (CPSC) | Passes |
| Heavy Metals ASTM F963 | Passes |
| Formaldehyde ASTM D6007 | Passes |
| Floor Score Certified California 01350 | Passes |
| Lead Scorecard EQ 4.3 Low-Emitting Materials | 1 Point |


Warranty

| Residential | Lifetime |
|------------------|----------|
| Light Commercial | 20 Years |
| Heavy Commercial | 15 Years |









Antimicrobial Surface Coating

Ceramic Bead Scratch Armor

20mil ScratchGuard Wear Layer


Natural Stone Texture

4.5mm High-Density Solid Core

1.5mm Sound-Reducing Underlayment

Antimicrobial Pad Protection







Get even better noise reduction with one of our FloorSilencer underlayments. You didn't hear it from us.