





Fairbanks 9534



Kodiak 9537



Alamo 9538



Cheyenne 9553



Stormy Sky 9557



Navajo 9563



Midnight Grey 9573



Yosemite 9599



EXACT-MATCH MOLDINGS

We are proud to provide robustly built, exact-match moldings and stair-finishing options for all of our Floating Floor lines. While other manufacturers only offer "coordinated" colors, our moldings blend perfectly.

YOU DIDN'T HEAR IT FROM US



69 HIIC **69**

64

24 ΔΙΙC

28AHIIC

61

Urban Surfaces is at the cutting edge of noise-reduction technology in multi-unit spaces. With scores like these, noise complaints will be a thing of the past.





WATERPROOF FLOORS WITH UNPARALLELED NOISE REDUCTION

Specifications



Specifications	Floating Floor
Product Type	Stone Polymer Composite
Core Material	4.5mm High-Density Solid Core
Wear Layer	20mil ScratchGuard
Embossing	Natural Wood Texture
Edge Profile	Beveled Edge
Overall Thickness	6mm (0.236")
Nominal Plank Size	7" x 48"
Actual Plank Size	182mm x 1220mm
Finish	Antimicrobial & Ceramic Bead
Attached Pad	1.5mm Sound-Reducing & Antimicrobial Pad
Clip System	Angle-Drop Clip System
Bacteria Resistance	Bioshield Coat
Testing	
Slip Resistance ASTM D2047	>0.52 (Dry)
Static Loading ASTM F970	2,000 PSI .036"
Radiant Flux ASTM E648	Class 1
Smoke Density ASTM E662	Passes
Light Resistance ASTM F1515	Passes
Heat Resistance ASTM F1514	Passes
Chemical Resistance ASTM F925	Passes
Phthalates ASTM F3414 - 20 (CPSC)	Passes
Heavy Metals ASTM F963	Passes
Formaldehyde ASTM D6007	Passes
Floor Score Certified California 01350	Passes
Lead Scorecard EQ 4.3 Low-Emitting Materials	1 Point
Warranty	
Residential	Lifetime
Light Commercial	20 Years
Heavy Commercial	15 Years

Floating Floor

