

SPECIFICATIONS

Product Line	Studio 12 Floating Floor
Product Type	Stone Polymer Composite
Core Material	4mm High-Density Solid Core
Wear Layer	12mil ScratchGuard
Overall Thickness	5mm (0.196")
Nominal Plank Size	7" x 48"
Actual Plank Size	182mm x 1220mm
Edge Profile	Beveled Edge
Embossing	Natural Wood Texture
Finish	Enhanced Polyurethane System
Installation Type	Floating
Clip System	Angle-Drop Clip System
Bacteria Resistance	Standard
Attached Pad	1mm Sound-Reducing Pad



CARTON	
Planks	10
Square Feet	23.90 sqft
Weight (lbs)	39.68 lbs
Square Meters	2.22 m2
Weight (kg)	18.00 kg

PALLET	
Cartons	55
Square Feet	1314.5 sqft
Weight (lbs)	2338 lbs
Square Meters	122.1 m2
Weight (kg)	1060.5 kg

CONTAINER	
Cartons	1,100
Square Feet	26290 sqft
Weight (lbs)	46759.99 lbs
Square Meters	2442 m2
Weight (kg)	21210 kg

PERFORMANCE TESTING

Slip Resistance	ASTM D2047	>0.69 (Dry)
Radiant Flux	ASTM E648	Class 1
Static Load	ASTM F970	2,000 PSI .011 Inch
Smoke Density	ASTM E662	Passes
Light Resistance	ASTM F1515	Passes
Heat Resistance	ASTM F1514	Passes
Chemical Resistance	ASTM F925	Passes
Phthalates	ASTM F3414 - 20 (CPSC)	Passes
Heavy Metals	ASTM F963	Passes
Formaldehyde	ASTM D6007	Passes
FloorScore Certified	California 01350	Passes
Leed Scorecard	EQ 4.3 Low-Emitting Materials	1 Point

WARRANTY



SOUND TESTING



Studio 12 Floating Floor
 Studio 12 Floating Floor + FloorSilencer Flex
 Studio 12 Floating Floor + FloorSilencer Boost

HIIC	IIC	LIIC	STC	ΔHIIC	ΔIIC
71	64	75	61	30	25
76	66	67	59	36	25
76	66	68	61	34	24

ARCHITECTURAL SPECIFICATION

All floors shown in the finish schedule or listed in the specification shall be Studio 12 Floating SPC Flooring provided by Urban Surfaces Inc., in design and color (list color TBD) selected from the range currently available from Urban Surfaces Inc, having a nominal total thickness of (Studio 12 Floating Floor- 5mm-0.196") gauge, and size in 7 in. x 48 in. (Studio 12 Floating Floor - 182 mm x 1220 mm) consisting of a (Studio 12 Floating Floor - 12 mil) thick Wear layer over a printed film. Flooring meets composition, size, thickness, squareness, flexibility, resistance to chemicals, resistance to heat and resistance to light requirements of ASTM F 1700, "Standard Specification for Solid Vinyl Tile," Class III, Type B - Embossed Surface. For Studio 12 Floating Floor, shall have a 10-Year Limited Light Commercial warranty against manufacturing defects. For Studio 12 Floating Floor, the Underlayment shall be FloorSilencer Flex/ FloorSilencer Boost/ FloorSilencer Pro For additional installation, maintenance, or technical information, visit our website at www.urbansurfaces.com or contact us at 1-800-492-8722. Please view actual product samples when making a selection as our printed colors may vary from actual product.

INSTALLATION

End Use:

Residential, Light Commercial

Suitable Grade Level:

All grades where excessive moisture conditions do not exist

Installation Method:

Direct Float, Click Lock System

Installation Sundries As Required:

FloorSilencer Boost, FloorSilencer Flex, FloorSilencer Pro

URBAN SURFACES
2380 RAILROAD STREET BUILDING 101 CORONA, CA
(800)492.8722