

SPECIFICATIONS

Product Line	Studio 12 Floating Floor	Finish	Enhanced Polyurethane System
Construction	Stone Polymer Composite (SPC)	Installation	Floating
Wear Layer	12 Mil ScratchGuard	Clip System	Rapid Lock
Embossing	Natural Wood Texture	Underlayment	Sound Reducing
Edge Profile	Beveled Edge	Sound Properties	STC 61 IIC 64 ΔIIC 22
Overall Thickness	5mm (0.196)	Bacteria Resistance	Standard
Plank Size	7 x 48		

PACKAGING

	Units	Square Feet	Weight (lbs)	Square Meters	Weight (kg)
Carton	10 Planks	23.47 sqft	41 lbs	2.18 m2	18.6 kg
Pallet	55 Cartons	1290.85 sqft	2255 lbs	119.92 m2	1022.85 kg
Container	1,100 Cartons	25817 sqft	45100 lbs	2398.48 m2	20457.02 kg

PERFORMANCE & TESTING

Slip Resistance	ASTM D2047	>0.69 (Dry)
Radiant Flux	ASTM E648	Class 1
Static Load	ASTM F970	2,000 PSI .011 Inch
Smoke Density	ASTM E662	Passes
Light Resistance	ASTM F1515	Passes
Heat Resistance	ASTM F1514	Passes
Chemical Resistance	ASTM F925	Passes
Phthalates	ASTM F3414 - 20 (CPSC)	Passes
Heavy Metals	ASTM F963	Passes
Formaldehyde	ASTM D6007	Passes
FloorScore Certified	California 01350	Passes
Leed Scorecard	EQ 4.3 Low-Emitting Materials	1 Point

WARRANTY

Residential	20 Years
Light Commercial	10 Years
Commercial	None