



SPECIFICATIONS

Product Line	Studio Floating Floor	Finish	Enhanced Polyurethane System
Construction	Stone Polymer Composite (SPC)	Installation	Floating
Wear Layer Thickness	12 Mil ScratchGuard	Clip System	RapidLock
Embossing	Natural Wood Texture	Underlayment	Sound Reducing
Edge Profile	Square Edge	Sound Properties	STC 61 IIC 66
Overall Thickness	5mm (0.2")	Bacteria Resistance	Standard
Size (Imperial)	7" x 48"	Size (Metric)	177.8mm x 1219.2mm

PACKAGING

Pieces per Carton	10	Cartons per Container	1100
Square Feet per Carton	23.47 sqft	Square Feet per Container	25817 sqft
Square Meters per Carton	2.18 m2	Square Meters per Container	2398.48 m2
Weight per Carton (Imperial)	41 lbs	Weight per Container (Imperial)	45100 lbs
Weight per Carton (Metric)	19 kg	Weight per Container (Metric)	20457 kg
Cartons per Pallet	55	Weight per Pallet (Imperial)	2255 lbs
Square Feet per Pallet	1290.85 sqft	Weight per Pallet (Metric)	1023 kg
Square Meters per Pallet	119.92 m2		

TESTING & SAFETY

Slip Resistance	ASTM D2047	>0.5 (DRY)
Radiant Flux	ASTM E648	CLASS 1
Smoke Density	ASTM E662	PASSES
Static Load	ASTM F970	PASSES
Light Resistance	ASTM F1515	PASSES
Heat Resistance	ASTM F1514	PASSES
Chemical Resistance	ASTM F925	PASSES
Phthalates	CPSC-CH-C1001-09.3	PASSES
Heavy Metals	ASTM F963	PASSES
Formaldehyde	Pending	Pending
FloorScore Certified	California 01350	PASSES
Leed Scorecard	Eq4.3 Low-Emitting Materials	

WARRANTY

Residential	20 Years
Light Commercial	10 Years
Commercial	None

