



SPECIFICATIONS

Product Line	Zeno PVC-Free Resilient GlueDown Flooring
	PVC-Free Resilient
Product Type	PVC-Free Resilient
Core Material	Polypropylene
Wear Layer	PVC-Free ScratchGuard - 12mil 20mil
Overall Thickness	3mm (0.118")
Nominal Plank Size	7" x 48"
Actual Plank Size	177.8mm x 1219.2mm
Edge Profile	Square Edge
Embossing	Natural Wood Texture
Finish	Enhanced Polyurethane
Installation Type	GlueDown
Adhesive To Use	3010 Prism, 3020 Everlast, or 3050 Omni
Wellness Assurance	Contains no PVC, plasticizers, phthalates,
	halogens, chlorines or heavy metals
Recycled Content	Polypropylene: 50% Pre-Consumer
	Food-Grade Material
Recyclability	100% Recyclable
Product Declarations	Third-Party Verified LCA



14

32.67 sqft

32.10 lbs

3.03 m2

14.56 kg

Planks

Square Feet

Weight (lbs)

Square Meters Weight (kg)

PALLET

Cartons 70 Square Feet 2286.9 sqft 2321.87 lbs Weight (lbs) Square Meters 212.1 m2 Weight (kg) 1053 kg

CONTAINER

Cartons 1120 Square Feet 36590.4 sqft Weight (lbs) 37149.84 lbs Square Meters 3393.6 m2 Weight (kg) 16848 kg

PERFORMANCE TESTING

Slip Resistance	ASTM D2047	>0.88 (Dry)
Radiant Flux	ASTM E648	Class 1
Static Load	ASTM F970	3000 psi 0.004 inch
Smoke Density	ASTM E662	Passes
Light Resistance	ASTM F1515	Passes
Heat Resistance	ASTM F1514	Passes
Chemical Resistance	ASTM F925	Passes
Phthalates	ASTM F3414 - 20 (CPSC)	Passes
Heavy Metals	ASTM F963	Passes
Formaldehyde	ASTM D6007	Passes
FloorScore Certified	California 01350	Passes
Leed Scorecard	EQ 4.3 Low-Emitting Materials	1 Point

WARRANTY





































SPECIFICATIONS

Product Line	Zeno PVC-Free Resilient GlueDown Flooring With Underlay
Product Type	PVC-Free Resilient
Core Material	Polypropylene
Wear Layer	PVC-Free ScratchGuard - 12mil 20mil
Overall Thickness	4mm (0.157")
Nominal Plank Size	7" x 48"
Actual Plank Size	177.8mm x 1219.2mm
Attached Underlay	1mm Sound-Reducing PET Underlay
Edge Profile	Square Edge
Embossing	Natural Wood Texture
Finish	Enhanced Polyurethane
Installation Type	GlueDown
Adhesive To Use	3010 Prism, 3020 Everlast, or 3050 Omni
Wellness Assurance	Contains no PVC, plasticizers, phthalates,
	halogens, chlorines or heavy metals
Recycled Content	Polypropylene: 50% Pre-Consumer
	Food-Grade Material
Recyclability	100% Recyclable
Product Declarations	Third-Party Verified LCA



Planks	14
Square Feet	32.67 sqft
Weight (lbs)	34.79 lbs
Square Meters	3.03 m2
Weight (kg)	15.78 kg

PALLET

 Cartons
 60

 Square Feet
 1960.2 sqft

 Weight (lbs)
 2160.53 lbs

 Square Meters
 181.8 m2

 Weight (kg)
 980 kg

CONTAINER

Cartons	910
Square Feet	29729.92 sqft
Weight (lbs)	32831.24 lbs
Square Meters	2762 m2
Weight (kg)	14892 kg

PERFORMANCE TESTING

Slip Resistance	ASTM D2047	>0.88 (Dry)
Radiant Flux	ASTM E648	Class 1
Static Load	ASTM F970	2000 psi 0.008 inch
Smoke Density	ASTM E662	Passes
Light Resistance	ASTM F1515	Passes
Heat Resistance	ASTM F1514	Passes
Chemical Resistance	ASTM F925	Passes
Phthalates	ASTM F3414 - 20 (CPSC)	Passes
Heavy Metals	ASTM F963	Passes
Formaldehyde	ASTM D6007	Passes
FloorScore Certified	California 01350	Passes
Leed Scorecard	EQ 4.3 Low-Emitting Materials	1 Point

WARRANTY



















LIGHT COMMERCIAL HEAVY COMMERCIAL









