

## **TEST REPORT**

<b>CLIENT</b> Urban Surface
-----------------------------

TEST METHOD CONDUCTED	ASTM	F386	Standard	Test	Method	for	Thickness	of	Resilient
	Flooring Materials Having Flat Surfaces								

DESCRIPTION OF TEST SAMPLE					
IDENTIFICATION	Zeno PVC Free				
CONSTRUCTION	PVC Free 3mm 7x48				

## **GENERAL PRINCIPLE**

The total thickness of a resilient flooring material is determined through measurements made using a .250 inch presser foot and a dial micrometer. The average of 5 total measurements is reported as the average total thickness.

## **TEST RESULTS**

SPECIMEN 1	0.124 inch	3.150 mm
SPECIMEN 2	0.123 inch	3.124 mm
SPECIMEN 3	0.124 inch	3.150 mm
SPECIMEN 4	0.122 inch	3.099 mm
SPECIMEN 5	0.125 inch	3.175 mm

AVERAGE TOTAL THICKNESS	0.124 inch	3.139 mm		
•	<del>-</del>			

APPROVED BY:

This report is provided for the exclusive use of the client to whom it is addressed. It may be used in its entirety to gain product acceptance from duly constituted authorities. This report applies only to those samples tested and is not necessarily indicative of apparently identical or similar products.

This report, or the name of Professional Testing Laboratory, LLC, shall not be used under any circumstance in advertising to the general public.

 $714\,Glenwood\,Place \qquad Dalton,\,GA\,30721 \qquad Phone:\,706-226-3283 \qquad Fax:\,706-226-6787 \qquad email:\,protest@optilink.us$