



URBAN  
SURFACES

# Stop LooseLay In Its Tracks.

Gripping Performance in Residential and Commercial Applications



Lose The Trowels! Easy Install With  
3/8" Short Nap Paint Roller

- 350 ft<sup>2</sup>/gal (1 Coat)
- 200 ft<sup>2</sup>/gal (2 Coats)



**90% RH**  
Moisture  
Protection



**10 lbs MVER**  
Moisture Vapor  
Emissions

- Fast Drying  
Formula

- Resealable With  
No Transfer

Non-Skid Coating  
Designed For Urban Surfaces  
InstaGrip LooseLay Flooring

**INSTAGRIP**  
LOOSELAY FLOORING



## Non-Skid Coating Designed for InstaGrip LooseLay Flooring

### Approved Substrates & Surfaces

- Concrete and radiant-heated subfloors that do not exceed 85° F.
- Gypsum and light-weight concrete (two coats of Traction recommended)
- APA underlayment-grade plywood and OSB (two coats of Traction recommended)

### Substrate Testing

One Coat	Two Coats
RH - 85% [ASTM F2170]	RH - 90% [ASTM F2170]
pH - 5-12	pH - 5-12
MVER - 5 lbs [ASTM F1869]	MVER - 10 lbs [ASTM F1869]
Porosity - Must Pass [ASTM F3191]	Porosity - Must Pass [ASTM F3191]

### Characteristics

Base Chemistry	Proprietary Latex Emulsion Blend
Curing Method	Air Dry
Appearance/Color	Milky-White
Odor	Extremely Low
Consistency	Low-Viscosity Liquid
Application	Easy Rolling
Flammability	Non-Flammable
Freeze/Thaw	Stable to 10°F (-12°C) [5 Cycles]
Shelf Life [Unopened Container at 70°F]	2 Years

### Testing

Moisture Control	Protect Flooring from 85% RH (1 Coat) or 90% (2 Coats) substrate moisture vapor
RH [ASTM F2170]	85% (1 Coat); 90% (2 Coats)
pH	5-12
MVER [ASTM F1869]	5 lbs (1 Coat); 10 lbs (2 Coats)
Porosity [ASTM F3191]	Must Pass (CSP 1+)

### Time

Working Time	24 hrs
Cure Time	2 hrs

### Sustainability

Solvents	No
Isocyanates	No
VOC Wet Applied [g/L] [SCAQMD Rule #1168]	<1 g/L
Bio-Based Content	No
Post-Consumer Recycled Content	No
Mineral-Abundant Content	No

### Warranty

Duration (Non CFI Certified)	10-Year Performance Warranty
Duration (CFI Certified)	Lifetime Performance Warranty
Coverage	85-90% Substrate Moisture Vapor