



10-YEAR LIMITED Warranty

Urban Surfaces provides a **10-year limited warranty** when Omni™ is used for the interior installation of approved flooring products over properly prepared substrates (see technical data sheet for complete details). Omni™ shall be free from manufacturing defect and when installed properly shall not delaminate due to substrate vapor or topical moisture.

Omni is capable of controlling concrete substrate moisture vapor with no RH, pH or MVER testing required. Substrates shall be properly prepared per ASTM F710, have no visible or standing moisture and be without hydrostatic pressure. When used as a concrete moisture vapor barrier, the substrate must also be properly prepared and porous per ASTM F3191. The installation must be performed following both the flooring manufacturer's and Urban Surfaces' guidelines. Please visit www.urbansurfaces.com for the latest product information and application instructions.

If an installation failure occurs as a direct result of the use of defective adhesive or delamination due to elevated moisture vapor or pH, Urban Surfaces will pay for equivalent floor covering, adhesive materials and for reasonable labor costs to repair or replace the failed portion of the installation as determined by Urban Surfaces at its sole discretion. This warranty applies only to the adhesive related bond failures. Urban Surfaces cannot warrant those variables over which it has no control such as the quantity of the adhesive used, the workmanship of the installer, the condition of the subfloor, the stability of the flooring product and its suitability for installation on the affected job-site, or any other conditions that might affect the installation.

Urban Surfaces reserves the right as deemed necessary to inspect any claim for cause or this warranty is null and void. Any repairs done prior to inspection by a Urban Surfaces representative voids any warranty. This warranty is non-transferable.