



## SPECIFICATIONS

<b>Product Line</b>	InstaGrip	<b>Finish</b>	Enhanced Polyurethane System
<b>Construction</b>	Luxury Vinyl Plank (LVP)	<b>Installation</b>	Minimal/Full Spread Adhesive
<b>Wear Layer Thickness</b>	28 Mil ScratchGuard	<b>Clip System</b>	N/A
<b>Embossing</b>	Natural Wood Texture	<b>Underlayment</b>	N/A
<b>Edge Profile</b>	Beveled Edge	<b>Sound Properties</b>	STC 61   IIC 48   ΔIIC 11
<b>Overall Thickness</b>	5mm (0.196")	<b>Bacteria Resistance</b>	N/A
<b>Size (Imperial)</b>	9" x 48"	<b>Size (Metric)</b>	228.6mm x 1219.2mm

## PACKAGING

<b>Pieces per Carton</b>	8	<b>Cartons per Container</b>	1040
<b>Square Feet per Carton</b>	24 sqft	<b>Square Feet per Container</b>	24960 sqft
<b>Square Meters per Carton</b>	2.23 m2	<b>Square Meters per Container</b>	2318.86 m2
<b>Weight per Carton (Imperial)</b>	41 lbs	<b>Weight per Container (Imperial)</b>	42640 lbs
<b>Weight per Carton (Metric)</b>	18.6 kg	<b>Weight per Container (Metric)</b>	19341.18 kg
<b>Cartons per Pallet</b>	52	<b>Weight per Pallet (Imperial)</b>	2132 lbs
<b>Square Feet per Pallet</b>	1248 sqft	<b>Weight per Pallet (Metric)</b>	967.06 kg
<b>Square Meters per Pallet</b>	115.94 m2		

## TESTING &amp; SAFETY

<b>Slip Resistance</b>	ASTM D2047	>0.8 (Dry)
<b>Radiant Flux</b>	ASTM E648	Class 1
<b>Static Load</b>	ASTM F970	2,000 PSI   .008 Inch
<b>Smoke Density</b>	ASTM E662	Passes
<b>Light Resistance</b>	ASTM F1515	Passes
<b>Heat Resistance</b>	ASTM F1514	Passes
<b>Chemical Resistance</b>	ASTM F925	Passes
<b>Phthalates</b>	ASTM F3414 - 20 (CPSC)	Passes
<b>Heavy Metals</b>	ASTM F963	Passes
<b>Formaldehyde</b>	ASTM D6007	Passes
<b>FloorScore Certified</b>	California 01350	Passes
<b>Leed Scorecard</b>	EQ 4.3 Low-Emitting Materials	1 Point

## WARRANTY

<b>Residential</b>	Lifetime
<b>Light Commercial</b>	Lifetime
<b>Commercial</b>	20 Years

