

**SPECIFICATIONS**

<b>Product Line</b>	Sound-Tec Tile	<b>Finish</b>	Anti-Microbial
<b>Construction</b>	Tri Core Stone Polymer Composite (SPC)		+ Ceramic Bead
<b>Wear Layer Thickness</b>	20 Mil ScratchGuard	<b>Installation</b>	Floating
<b>Embossing</b>	Natural Wood Texture	<b>Clip System</b>	RapidLock
<b>Edge Profile</b>	Beveled Edge	<b>Underlayment</b>	Sound Reducing + Anti-Microbial
<b>Overall Thickness</b>	6mm (0.236")	<b>Sound Properties</b>	STC 61   IIC 66
<b>Size (Imperial)</b>	12" x 24"	<b>Bacteria Resistance</b>	Bioshield Coat
<b>Size (Metric)</b>	304.8mm x 609.6mm		

**PACKAGING**

<b>Pieces per Carton</b>	12	<b>Cartons per Container</b>	1,026
<b>Square Feet per Carton</b>	24 sqft	<b>Square Feet per Container</b>	24624 sqft
<b>Square Meters per Carton</b>	2.23 m2	<b>Square Meters per Container</b>	2287.64 m2
<b>Weight per Carton (Imperial)</b>	45 lbs	<b>Weight per Container (Imperial)</b>	46170 lbs
<b>Weight per Carton (Metric)</b>	20.41 kg	<b>Weight per Container (Metric)</b>	20942.36 kg
<b>Cartons per Pallet</b>	54	<b>Weight per Pallet (Imperial)</b>	2430 lbs
<b>Square Feet per Pallet</b>	1296 sqft	<b>Weight per Pallet (Metric)</b>	1102.23 kg
<b>Square Meters per Pallet</b>	120.40 m2		

**TESTING & SAFETY**

<b>Slip Resistance</b>	ASTM D2047	>0.52 (DRY)
<b>Radiant Flux</b>	ASTM E648	CLASS 1
<b>Smoke Density</b>	ASTM E662	PASSES
<b>Static Load</b>	ASTM F970	2,000 PSI   .036 INCH
<b>Light Resistance</b>	ASTM F1515	PASSES
<b>Heat Resistance</b>	ASTM F1514	PASSES
<b>Chemical Resistance</b>	ASTM F925	PASSES
<b>Phthalates</b>	CPSC-CH-C1001-09.3	PASSES
<b>Heavy Metals</b>	ASTM F963	PASSES
<b>Formaldehyde</b>	ASTM D6007	PASSES
<b>FloorScore Certified</b>	California 01350	PASSES
<b>Leed Scorecard</b>	Eq4.3 Low-Emitting Materials	1 POINT

**WARRANTY**

<b>Residential</b>	Lifetime
<b>Light Commercial</b>	20 Years
<b>Commercial</b>	15 Years

THE MODERN FLOORING SOLUTION