

## SPECIFICATIONS

|                             |   |                            |                                    |
|-----------------------------|---|----------------------------|------------------------------------|
| <b>Product Line</b>         | Sound-Tec                                 | <b>Finish</b>              | Anti-Microbial<br>+ Ceramic Bead   |
| <b>Construction</b>         | Tri Core Stone Polymer<br>Composite (SPC) |                            |                                    |
| <b>Wear Layer Thickness</b> | 20 Mil ScratchGuard                       | <b>Installation</b>        | Floating                           |
| <b>Embossing</b>            | Natural Wood Texture                      | <b>Clip System</b>         | RapidLock                          |
| <b>Edge Profile</b>         | Beveled Edge                              | <b>Underlayment</b>        | Sound Reducing<br>+ Anti-Microbial |
| <b>Overall Thickness</b>    | 6mm (0.236")                              |                            |                                    |
| <b>Size (Imperial)</b>      | 7" x 48"                                  | <b>Sound Properties</b>    | STC 61   IIC 66                    |
| <b>Size (Metric)</b>        | 177.8mm x 1219.2mm                        | <b>Bacteria Resistance</b> | Bioshield Coat                     |

## PACKAGING

|                                     |             |  |             |
|-------------------------------------|-------------|--|-------------|
| <b>Pieces per Carton</b>            | 10          | <b>Cartons per Container</b>           | 1,000       |
| <b>Square Feet per Carton</b>       | 23.47 sqft  | <b>Square Feet per Container</b>       | 23470 sqft  |
| <b>Square Meters per Carton</b>     | 2.18 m2     | <b>Square Meters per Container</b>     | 2180.43 m2  |
| <b>Weight per Carton (Imperial)</b> | 44.09 lbs   | <b>Weight per Container (Imperial)</b> | 44090 lbs   |
| <b>Weight per Carton (Metric)</b>   | 20 kg       | <b>Weight per Container (Metric)</b>   | 19998.89 kg |
| <b>Cartons per Pallet</b>           | 50          | <b>Weight per Pallet (Imperial)</b>    | 2204.5 lbs  |
| <b>Square Feet per Pallet</b>       | 1173.5 sqft | <b>Weight per Pallet (Metric)</b>      | 999.94 kg   |
| <b>Square Meters per Pallet</b>     | 109.02 m2   |  |             |

## TESTING & SAFETY

|                             |                              |                       |
|-----------------------------|------------------------------|-----------------------|
| <b>Slip Resistance</b>      | ASTM D2047                   | >0.52 (DRY)           |
| <b>Radiant Flux</b>         | ASTM E648                    | CLASS 1               |
| <b>Smoke Density</b>        | ASTM E662                    | PASSES                |
| <b>Static Load</b>          | ASTM F970                    | 2,000 PSI   .036 INCH |
| <b>Light Resistance</b>     | ASTM F1515                   | PASSES                |
| <b>Heat Resistance</b>      | ASTM F1514                   | PASSES                |
| <b>Chemical Resistance</b>  | ASTM F925                    | PASSES                |
| <b>Phthalates</b>           | CPSC-CH-C1001-09.3           | PASSES                |
| <b>Heavy Metals</b>         | ASTM F963                    | PASSES                |
| <b>Formaldehyde</b>         | ASTM D6007                   | PASSES                |
| <b>FloorScore Certified</b> | California 01350             | PASSES                |
| <b>Leed Scorecard</b>       | Eq4.3 Low-Emitting Materials | 1 POINT               |

## WARRANTY

|                         |          |
|-------------------------|----------|
| <b>Residential</b>      | Lifetime |
| <b>Light Commercial</b> | 20 Years |
| <b>Commercial</b>       | 15 Years |

THE MODERN FLOORING SOLUTION